

FS120

2 HOUR RATED FIRE SHUTTER :: TECHNICAL DATASHEET



The FS120 fire shutter was tested by WarringtonFire and is certified by Element Materials Technology (Notified Body no. 2812) for 2 hours of fire protection (report no 419785 and extension report no 428745). It meets the standards BS EN 16034:2014 for fire resistance characteristics and BS EN 13241:2003 + A2 2016 for non-fire performance.



APPLICATIONS

The Fireroll FS120 fire shutter has been tested by Warringtonfire to ensure they maintain 120 minute integrity in the event of a fire. Fire shutters operate automatically in the event of an alarm signal, providing reliable compartmentalisation and enhancing safety and security.

Fusible link and solenoid release allow the shutter to automatically descend in the event of an emergency while a battery back-up ensures this function is maintained in the event of a power outage. All shutters can be integrated into a fire alarm system as required.

CURTAIN SLAT

Single skin 76mm curved steel.

Finish: Galvanised finish as standard. Option to powder coat any RAL / BS colour (surcharges apply).

Visible Face:	76mm
Weight per m ² :	9.8kg
Maximum Width:	4000mm*
Maximum Area:	14.25m ² *

*Size limitations vary dependent on motor

CASING

Galvanised steel casing & end plates as standard. Reveal fix installations are supplied with a fascia as standard. Finish: Galvanised finish as standard. Option to powder coat any RAL / BS colour.

Guide Height (mm)	Plate Size (mm)
2695	305
4000	355
5000	400
6500	400
7000	450
8000	500

All plate sizes are shown as a guide only.

BOTTOM RAIL

Galvanised steel 'T' shaped bottom rail.

GUIDE CHANNELS

Galvanised steel guide channels. Width of 65mm or 100mm.

Finish: Galvanised finish as standard. Option to powder coat any RAL / BS colour (surcharge applies).

OPERATION

Tubular Motor: Ellard tubular motor, audio-visual interface panel and battery back up facility.

Inline Motor: Single phase inline chain driven motor (three phase option available) with push button control audio-visual panel, chain override, fusible link and solenoid release.

All Fireroll fire shutters can be connected into fire alarms and building management systems as required.




FS120

2 HOUR RATED FIRE SHUTTER :: TECHNICAL DATASHEET



TUBULAR MOTOR

Face fit examples shown. Drawings will vary for reveal fit installations.



INLINE MOTOR

Face fit examples shown. Drawings will vary for reveal fit installations.

